

MCB128

Quiz b3

March 13, 2026


Name: _____

Score: _____

Instructions:

- Show all work for full credit.
- Can check notes; no prompts to chatbot allowed

1. (3 pts) For a system of L inputs of length D , producing L outputs of length D ,
- (1 pts) In a self-attention mechanism, calculate the number of weights and biases used to compute queries, keys, and values.
 - (1 pts) Calculate the number of weights and biases to go from the same (L,D) inputs to the same (L,D) outputs by a fully connected single layer (by flattening).
 - (1 pts) Compare the two outcomes with respect to the size of the input L .



(a)

$$\text{queries} : W^Q[D, d_k] \quad b^Q[d_k]$$

$$\text{keys} : W^K[D, d_k] \quad b^K[d_k]$$


$$\text{values} : W^V[D, d_v] \quad b^V[d_v]$$

Total number of parameters $2(D \times d_k + d_k) + (D \times d_v + d_v)$
If $d_k = d_v = D$, it becomes $3(D^2 + D)$.


(b) $inputs[L, D] \rightarrow outputs[L, D]$,

thus weights have dimensions $(L \times D) \times (L \times D) = L^2 \times D^2$.

(c) For the FCL, the parameters depend on input length L , which forces all inputs to have the same length, and it scales with L^2 which can be quite costly in memory requirements.



(e) triangle self-attentions



2. (7 pts) Calculate the size of the self-attention maps for each of the following cases. Outputs have the same dimensions than the inputs.

- (a) (1 pts) A sequence embedding $x[L, D]$
 $sa[L, L]$
- (b) (2 pts) An alignment embedding $m[L, S, D]$
 $sa[L, S, L, S]$ with general self-attention
- (c) (2 pts) An alignment embedding $m[L, S, D]$ with self-attention by rows
 $sa[L, L, S]$
- (d) (2 pts) An alignment embedding $m[L, S, D]$ with self-attention by columns
 $sa[S, S, L]$
- (e) (bonus pts) AlphaFold2 triangle self-attention on pair representation $z[r, r, c_z]$, (see Figure 12, right)
 $sa[r, r, r]$